PATTINT COOPERATION TREAT

To:

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

Commissioner **US Department of Commerce** United, States Patent and Trademark Office, PCT 2011 South Clark Place Room

CP2/5C24 Arlington, VA₁22202

ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 15 November 2000 (15.11.00)

International application No. PCT/GB00/01160

International filing date (day/month/year)

27 March 2000 (27.03.00)

Applicant's or agent's file reference DE/J088373PWO

Priority date (day/month/year) 26 March 1999 (26.03.99)

Applicant

ROBINSON, John

			/ /	
X in the demand filed wit	th the International	Preliminary Exar	mining Authority on:	the state of the s
· ·	24 Oc	tober 2000 (2	4.10.00)	- Control of the state of the s
in a notice effecting lat	: er election filed wit	h the Internation	al Bureau on:	
	•			
			: 1	
The election X was	: -			
was no	t	:		da siraame et et
made before the expiration o	f 19 months from th	ne priority date o	r, where Rule 32 ap	olies, within the time limit under
Rule 32.2(b).				
•				
•				

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland

Authorized officer

Zakaria EL KHODARY

Telephone No.: (41-22) 338.83.38

Facsimile No.: (41-22) 740.14.35



PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference		
DE/J088373PWO	FOR FURTHER ACTION See	Notification of Transmittal of International liminary Examination Report (Form PCT/IPEA/416)
International application No. PCT/GB00/01160	International filing date (day/month/year) 27/03/2000	Priority date (day/month/year) 26/03/1999
International Patent Classification (IPC) or national A23F3/40	ional classification and IPC	
Applicant DYNAMIC PRODUCTS LIMITED et a	ai.	
This international preliminary examinand is transmitted to the applicant actions.	nation report has been prepared by the ecording to Article 36.	is International Preliminary Examining Authority
2. This REPORT consists of a total of	4 sheets, including this cover sheet.	
peen amended and are the basis	by ANNEXES, i.e. sheets of the desc s for this report and/or sheets contain 7 of the Administrative Instructions un	cription, claims and/or drawings which have ing rectifications made before this Authority der the PCT).
These annexes consist of a total of 5	•	
This report contains indications relations	ng to the following items:	
I ⊠ Basis of the report		
III Non-establishment of opi	nion with regard to novelty, inventive	step and industrial applicability
V ⊠ Reasoned statement und		r, inventive step or industrial applicability;
VI Certain documents cited		
VII Certain defects in the inte		
VIII ☐ Certain observations on t	he international application	
Date of submission of the demand	Date of completi	on of this report
24/10/2000	15.05.2001	
Name and mailing address of the international preliminary examining authority:	Authorized office	ESTON SOVES AND THE
European Patent Office D-80298 Munich Tel. +49 89 2399 - 0 Tx: 523656 ep Fax: +49 89 2399 - 4465		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	Telephone No. +	49 89 2399 8655

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No. PCT/GB00/01160

. Basis	of the	report
---------	--------	--------

1.	tne an	e receiving Office in	nents of the international ap response to an invitation und o this report since they do no	der Article 14 are	referred to in this	report as "originally filed"
	1,2	2,5-9	as originally filed			
	3,4		as received on	30/04/2001	with letter of	24/04/2001
			•			
	Cla	aims, No.:	•			
	1-1	8.	as received on	30/04/2001	with letter of	24/04/2001
		•			•	
			•			`
2.	Wit lan	th regard to the lang guage in which the i	juage, all the elements mark nternational application was	ed above were a filed, unless othe	vailable or furnishe erwise indicated un	ed to this Authority in the oder this item.
	The	ese elements were a	available or furnished to this	Authority in the fo	ollowing language:	, which is:
		the language of a t	translation furnished for the p	ourposes of the in	nternational search	(under Rule 23 1/h))
			blication of the international			(5),
			translation furnished for the p			y examination (under Rule
3.	Witl	h regard to any nuc rnational preliminary	leotide and/or amino acid s y examination was carried ou	sequence disclosut on the basis of	sed in the internation the sequence listing	onal application, the
		contained in the int	ernational application in writt	ten form.		,
			he international application i		able form.	
			ently to this Authority in writte			
		furnished subseque	ently to this Authority in comp	puter readable fo	rm.	
		The statement that	the subsequently furnished oplication as filed has been fu	written sequence		beyond the disclosure in
		The statement that listing has been fur	the information recorded in on inshed.	computer readab	le form is identical	to the written sequence
	The	amendments have	resulted in the cancellation o	of:		
		the description,	pages:			
		the claims,	Nos.:			
		the drawings,	sheets:			•



International application No. PCT/GB00/01160

	Rea	soned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; ions and explanations supporting such statement
6.	Addi	itional observations, if necessary:
		(Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report.)
5.		This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

1. Statement

Novelty (N)

Yes:

Claims 1-18

No:

Claims

Inventive step (IS)

Yes:

Claims 1-18

No: Claims

Industrial applicability (IA)

Yes:

Claims 1-18

No: Claims

2. Citations and explanations see separate sheet

Re Item V

1) Reference is made to the following documents:

D1: DATABASE WPI Section Ch, Week 198645, Derwent Publications Ltd., London, Class D13, AN 1986-293635 & HU-A-0 039 343 (CYCLOPACK KUTATASI)

D2: EP-A-0 284 790 (FIRMENICH S.A.)

Document D1 discloses a process for the preparation of a cellulosic carrier 2) material (tea bags) comprising the steps of: i) preparing a "cyclodextrin inclusion complex" of a flavouring substance (= flavouring particles encapsulated in a polysaccharide material); ii) providing an aqueous suspension comprising said inclusion complex (8-30% w/w) and binders (0.1-5.0% w/w); and iii) binding said particles to filter paper by impregnation, i.e by application of said aqueous suspension to the filter paper, followed by drying (see abstract).

Document D2 describes a process wherein an emulsion of particles (droplets) of a flavouring compound encapsulated within a water soluble polysaccharide material (e.g. starch or natural gums) having adhesion properties are bound to a porous carrier such as a cellulosic package material (tea bags), whereby the application of the emulsion to the carrier material is carried out by spraying, soaking or steeping (see p.2, I.35 to p.3, I.49; and example 4).

None of the prior art documents cited in the International Search Report anticipates or suggests dosing the encapsulated particles onto the carrier by means of a metered printing process. Therefore, the subject-matter as claimed appears to comply with the requirements of novelty (Article 33(2) PCT) and inventive step (Article 33(3) PCT).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	ТJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	TE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JР	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
СН	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		
							-



FLAVOURING OR AROMATISATION OF AN INFUSION

The present invention relates to a method for the flavouring or aromatisation of an infusion and more particularly to a method for producing a product that is used to make a flavoured or aromatized infusion such as, for example, a tea beverage.

It is well known to flavour or aromatise vegetable matter with natural or synthetic flavours. In the case of tea, the leaves are often flavoured or aromatised with essential oils such as bergamot or jasmine or, in some countries, spices such as mint or cardamom. In recent years there has been an increase in popularity of fruit flavoured teas such as, for example, strawberry, raspberry, lemon, blackcurrant or peach.

Flavouring or aromatisation is also used in some instances to prolong the storage life of tea without impairing its taste.

Flavouring of tea can be performed by spraying a liquid flavour in an inert edible solvent directly on to a fluidised bed of tea leaves. An example of this technique is described in EP-A-0070719. However, this method has a disadvantage in that the flavouring solution has a tendency to evaporate from the surface of the sprayed leaves during subsequent drying, storage, transportation or handling. The evaporation of the solution leads to the loss of the top notes of flavour in the resulting infusion.

In an alternative method the flavouring takes the form of solid particles that are mixed with the tea leaves on a fluidised bed (as referred to above). A disadvantage of this method is that there is a tendency for the flavour particles to separate from the leaves under the effect of gravity during storage, transportation or handling. In addition, the flavour particles tend to egress through the walls of the tea bags in which they are contained.

In both the aforementioned methods the disadvantages lead to a tea product that has a non-uniform flavour.

US-A-4880649 describes a process for flavouring an edible composition in the form of leaves, powders or particles. The composition is flavoured with an emulsion containing an active volatile flavouring substance that is non-miscible with water. The

emulsion is applied by direct spraying on to the exposed surface of the composition or a carrier package for the composition (such as a tea-bag or a filter) and comprises the flavouring substance, an aqueous solution of a film-building water soluble vehicle and an emulsifying agent. The flavouring substance is initially retained on the surface of the composition by adhesion of the emulsion as a result of the bonding effect of the film-building vehicle. After the sprayed composition is dried (for example, by evaporation or absorption of the water used in preparing the emulsion) the flavouring substance is incorporated within a protective water-soluble dry layer of the film-building vehicle. In use, when the sprayed composition or carrier is immersed in water the film-building vehicle dissolves in water so as to release the flavouring substance. A disadvantage of this process is that the flavour may not be uniformly distributed throughout the composition. Whilst the method does address part of the problem of flavour evaporation, some of the flavouring substance that is exposed at the surface of the film coating will nevertheless evaporate during the drying process.

EP-A-0499858 describes a process for the aromatisation of vegetable matter such as tea using particulate micro-encapsulated flavour. Micro-encapsulated flavour powders are produced by spray-drying as a liquid on to a maltodextrin support and the particles are sieved so as to remove the smallest. Peanut oil is then mixed with the flavour particles to provide a coating which increases the particle size and the tendency of the particles to agglomerate. The coated flavour is mixed with the tea leaves and placed within tea bags. The coated, agglomerated particles are too large to egress through the walls of the tea bag material during packing and handling. When the bag is infused the peanut oil is dispersed and the flavour is released so as to pass through the bag material. This process has several disadvantages. First, the strength of a particular infusion depends on the distribution of the mix prior to bagging. The coated flavour particles will tend to separate from the tea leaves under gravitational action prior to bagging, particularly during transportation. Moreover, the peanut oil tends to pass through the bag during the infusion process and may influence the flavour or appearance of the infused beverage. In addition, since a tea manufacturer will generally produce a range of teas with different flavours the tea leaves are generally mixed with the flavouring in relatively small batches and there is a risk of cross-contamination between batches having different flavourings.

It is an object of the present invention to obviate or mitigate the aforesaid disadvantages.

According to a first aspect of the present invention there is provided a process for the flavouring or aromatisation of product to be infused comprising the steps of producing encapsulated flavour particles, bonding the particles to a porous carrier and introducing the product into the carrier.

The term "particle" or "particles" is used herein to cover an encapsulated solid particle or liquid droplet of flavouring.

The terms "capsule", "encapsulant", "encapsulated" and "micro-encapsulated" are used herein to refer to any flavour oil bound within a flavour carrying matrix, regardless of whether said matrix forms a capsule in the classical sense.

The carrier may be constructed of cellulose-based material such as that used in the manufacture of tea bags. It may be constructed, for example, of cellulose or a mixture of cellulose material and a polyolefin.

Preferably the particles are applied to the carrier using a dosing process to control the distribution of particles on the carrier. The dosing process may be a metered printing process by which the quantity of particles per unit of surface area of the carrier material can be controlled. The particles may be suspended or in a liquid solution for this purpose.

The flavour may be conveniently encapsulated in a polysaccharide so that the capsule has adhesive properties that allow it to bond to the carrier. In one preferred embodiment the polysaccharide is a modified starch and more preferably an n-octyl-succinate modified starch.

Preferably the capsule is soluble in water within a predetermined temperature range. Alternatively the flavour is encapsulated by a capsule that is frangible within a pre-determined temperature range so that the flavour is released when infused in fluid within or above that particular temperature range.

The flavouring in the capsule is conveniently designed to increase in internal vapour pressure within said pre-determined temperature range so as induce rupture of said capsule. In addition, or in the alternative, the capsule may have a gum-based coating that is designed to weaken in said temperature range so as to induce rupture of said capsule.

According to a second aspect of the present invention there is provided an infusion product comprising a porous carrier containing matter to be infused and encapsulated flavour particles bonded to said carrier.

According to a third aspect of the present invention there is provided a porous product carrier to which are bonded encapsulated flavour particles.

In a first embodiment micro-encapsulated flavouring particles are formed by a known coascervation method and are dissolved in an aqueous solution. Each capsule contains flavouring oils and is hermetically sealed by an outer wall of entirely edible gel or gum-based material. The size of the capsule is accurately determined during manufacture so that the concentration of the flavouring oil in use is controlled.

The micro-encapsulated particles are applied to a porous cellulosic (or a combination of cellulose and polyolefin) material from which tea-bags or the like are manufactured by a known dosing process such as metered printing (e.g. rotogravure printing). After printing, the water is absorbed, dried and/or evaporates leaving the capsules bonded to the surface of the material. The capsules are designed not to rupture under external mechanical stress during processing.

The material is then cut into tea bag form, filled with tea leaves and sealed in a conventional manner.

In use, the tea-bag is infused in hot water in the usual way. As the capsules are heated by the water there is a continual weakening of the capsule wall strength and simultaneously a continual increase in the internal vapour pressure of the flavoured oil within the capsule. When the temperature of the capsule is within a predetermined temperature range the combined effect of increasing internal pressure and the weakening of the capsule walls results in catastrophic failure of the capsule material.

5

The oil is instantaneously released, passes through the tea bag material and into the water. The capsule material is designed to dissolve in the water after rupture.

There are many advantages to using the process of the present invention in the production of flavoured products (such tea) for infusion. First, the amount of flavouring oil per tea bag can be carefully controlled as a result of the microencapsulation process and dosing process. The micro-encapsulation process provides careful metering of the size of oil droplet in each capsule. If an engraved metering roller (such as that used in gravure printing) is used in the printing process to apply the particles to the bag material the quantity of capsules per unit surface area of the bag material can be controlled. The control of the capsule size and their distribution over the bag enables tea-bags to be produced with flavour characteristics that are reproducible between batches. Secondly, since there is no need to subject the tea leaves to a flavour coating or mixing process not only is the tea production procedure simplified but also there is no risk of cross contamination of flavours between batches of tea. Indeed the tea can be bagged in larger batch sizes in view of the elimination of the mixing or coating stage. Thirdly, the elimination of evaporation of the flavouring oil by using hermetically sealed capsules prevents the loss of top notes of flavour. Notwithstanding this, the oil can be pre-treated by, for example, heating to remove the flavour top notes prior to encapsulation if it is desired to simulate the flavour of a conventional tea infusion.

The micro-encapsulation of the flavouring oil ensures that it is hermetically sealed so that if the tea bag is used after prolonged storage the flavour of the infusion remains fresh without the need for special flavour-retaining packaging.

In a second embodiment the flavour is encapsulated in a modified starch compound, preferably an n-octyl succinate modified starch, which may or may not be pre-gelatinised, by mixing, preferably high shear mixing, in an aqueous environment. Further ingredients, such as a weighting agent, preservative and/or citric acid may also be added. Preferred weighting agents are sucrose esters, especially sucrose acetate isobutyrate, rosin esters and polyol bezoates, preferred preservatives are sodium benzoate or potassium sorbate. Citric acid may be added in various quantities

dependent upon the desired tartness of the finished product. The weighting agent, if used, is mixed with the flavouring oil prior to encapsulation by the starch, the resulting mixture being neutrally buoyant with respect to water, to reduce further any tendency the emulsion may have for separation.

The encapsulated flavour oil mixture is then applied (possibly in diluted form) to a porous cellulosic (or a combination of cellulose and polyolefin) material from which tea bags or the like are manufactured by a known dosing process such as metered printing. After printing the water is absorbed, dried and/or evaporates leaving the starch bound to the surface of the cellulosic material, with the flavour oil entrained by the starch.

In use, a tea bag made from material treated in this manner is infused in hot water. As the starch is heated it becomes detached from the tea bag material and solubilises the flavour oil into the body of the beverage, thus releasing the flavour oil into the drink.

The process of the present invention provides for a simplified procedure for producing an infusion product with improved quality.

Specific embodiments of the present invention will now be described, by way of illustration only, with reference to the following example.

EXAMPLE 1

A batch of earl grey tea was made using bergamot oil as the flavouring. A coascervation micro-encapsulation process was performed using 1 kg of bergamot oil and 5.02kg of other ingredients (principally de-ionised water) to form 6.02kg of aqueous solution with micro-capsules. A quantity of 0.3% to 5% of colloids comprising a suitable non-toxic food-safe natural gum and a specific gelatine with a suitable isoelectric point were dissolved in 40% to 90% of deionized water and conditioned with suitable reagents including emulsifiers. Following a brief period of heating to 26°C to 60°C, a quantity of 5% to 50% of bergamot oil was rapidly added and sufficiently agitated to produce droplets of an average diameter of 15μ (the majority being within a range of 5 to 25μ). The resulting mixture is adjusted to a pH level of between 4.2 and 8.0 to induce a controlled precipitation of the colloids at the

boundary between the water and the bergamot oil. Following a period of stirring, the mixture was allowed to cool gradually to ambient temperature and then force-chilled to 5 to 18°C leaving a plurality of capsules filled with droplets of bergamot oil. Following a further period of stirring of 10 to 90 minutes 0.5% to 15% of a rheology modifying natural gum colloid was added and dispersed so as to form a first coating over the existing capsules. Thereafter 0.05% to 15% of rheology modifying gum was added and dispersed to form a second coating over the outside of the first coating. This gum may or may not be the same as that mentioned above and is again non-toxic and food-safe. The first and second coatings of the capsules facilitate application of the capsules to the tea bag material during a subsequent dosing process described below and dictate the strength of bond of the capsule to the tea bag material.

The tea bag material was manufactured in a conventional manner and the solution of micro-encapsulated droplets was applied thereto in measured doses by a flexographic printing process. In the particular process used here an "inking" roller turns within a reservoir of solution (which is constantly agitated). The gum coatings on the capsules enable them to adhere to the inking roller so that they are pulled out of the reservoir by the roller which then applies the solution to an Anilox micro-engraved metering roller with which it is in circumferential contact. The solution is distributed into discrete doses in the engraved patterns of the roller. The Anilox roller then transfers the doses of solution to a printing roller by which they are applied to the tea bag material. In this example, the metering of the solution was such that a wet film weight of 2g/square metre was applied. This equates to an oil distribution of 0.34g per square metre.

The printing roller ensures that the capsules are pressed into intimate contact with the tea bag material so that they are embedded into the material fibres. The gums within the capsule coatings ensure effective adhesion of the capsules to a plurality of fibres of the material.

Once printed, the majority of the water is absorbed into the tea bag material although some may evaporate during and after the printing process.

The bag material was then formed, filled and sealed using conventional apparatus and processes. Tea-bags of 65 square millimetres were formed. With each bag having two sides the total surface area of each bag was 0.00845 m² and therefore an average 0.00287g of flavouring oil per bag was applied. The tea bag was filled with approximately 2.2g of tea leaves before being sealed.

The infused tea bag gave a brew of similar strength to teas manufactured according to conventional methods but without the loss of top notes of the flavouring oil.

In a second embodiment the micro-encapsulated flavouring particles are formed by compounding a suitable polysaccharide such as a modified starch or cyclodextrin with the flavouring oil and are then suspended in an aqueous solution to form a printable solution as before.

A specific embodiment of the micro-encapsulating process is described, by way of example only, with reference to the following example.

EXAMPLE 2

An n-octyl succinate modified starch grade, having both hydrophilic properties conferred by the hydroxyl groups along the starch backbone and hydrophobic properties conferred by the n-octyl succinate modifications, was used in attempt to form encapsulated flavour units in a aqueous environment as described below.

25g of modified starch was dissolved in 75g of water at room temperature. A flavouring oil (lemon) was added to the solution, with stirring, in a starch:oil ratio of between 6:1 and 1.5:1. Homogenisation of the resulting emulsion produces a stable emulsion, with no visible separation over prolonged standing. The emulsions resulting from homogenisation were found to be of higher viscosity than desirable for subsequent printing, but it was found that the viscosity could be reduced simply by addition of extra water.

The encapsulated flavour units are thus already in an aqueous delivery system, which is suitable for printing directly on to the tea bag material, the polysacharride backbone of the modified starch adhering to the cellulosic material of the bag. When

the tea bag is infused, the encapsulated flavour units start to break down resulting in the flavour oil being released gradually into the infusion.

It will be appreciated that the present invention has application not only to tea bags but also other infusions in which a product to be infused is held by a porous carrier. For example, filter papers used in the brewing of coffee or other beverages.

It will also be understood that any appropriate controlled dosing process may be used to apply the encapsulated particles in solution to the tea bag material. For example, spraying may be used without risk of evaporation of the flavouring. Moreover, there are many alternative metered printing configurations that may be used instead of that described in the example described herein. These alternatives will be evident to the skilled person in the art.

CLAIMS

- 1. A process for the flavouring or aromatisation of product to be infused comprising the steps of producing encapsulated particles of flavour, bonding the particles to a porous carrier and introducing the product into the carrier.
- 2. A process according to claim 1, wherein the carrier is a cellulose-based material.
- 3. A process according to claim 1 or 2, wherein the particles are applied to the carrier using a dosing process to control the distribution of particles on the carrier.
- 4. A process according to claim 3, wherein the dosing process is a metered printing process.
- 5. A process according to any preceding claim, wherein the flavouring is encapsulated by a capsule that is soluble in water within a predetermined temperature range.
- 6. A process according to any preceding claim, wherein the flavour is encapsulated in a polysaccharide that has adhesive properties.
- 7. A process according to claims 5 or 6 wherein the polysaccharide is a modified starch.
- 8. A process according to claim 7 wherein the polysaccharide starch is an n-octyl succinate modified starch.



- 9. A process according to any one of claims 1 to 4, wherein the flavouring is encapsulated by a capsule that is frangible within a pre-determined temperature range.
- 10. A process according to claim 9, wherein the flavouring in the capsule is designed to increase in internal vapour pressure within said pre-determined temperature range so as induce rupture of said capsule.
- 11. A process according to claim 9 or 10, wherein the capsule has a gum-based coating that is designed to weaken in said temperature range so as to induce rupture of said capsule.
- 12. An infusion product comprising a porous carrier containing matter to be infused and encapsulated flavour particles bonded to said carrier.
- 13. An infusion product according to claim 12, wherein the encapsulated flavour particles comprise an outer capsule of polysaccharide with adhesive properties.
- 14. An infusion product according to claim 13, wherein the polysaccharide is a modified starch.
- 15. An infusion product according to claim 14 wherein the modified starch is an noctyl succinate modified starch.
- 16. An infusion product according to claim 13, wherein the polysaccharide is a natural gum.
- 17. An infusion product according to claim 16, wherein the capsule is frangible within a predetermined temperature range.

- 18. An infusion product according to claim 17, wherein the flavouring in the capsule is designed to increase in internal vapour pressure within said predetermined temperature range so as to induce rupture of said capsule.
- 19. An infusion product according to claim 17 or 18 wherein the capsule has a gum-based coating that is designed to weaken in said temperature range so as to induce rupture of said capsule.



AMENDED CLAIMS

[received by the International Bureau on 24 August 2000 (24.08.00); original claims 1, 3, 7, 8, 9, 12 and 15 amended; other claims unchanged (3pages)]

- 1. A process for the flavouring or aromatisation of product to be infused comprising the steps of producing encapsulated particles of flavour, bonding the particles to a porous carrier using a dosing process to control the distribution of particles on the carrier, and introducing the product into the carrier.
- 2. A process according to claim 1, wherein the carrier is a cellulose-based material.
- 3. A process according to claim 1 or 2, wherein the dosing process is a metered printing process.
- 4. A process according to any preceding claim, wherein the flavouring is encapsulated by a capsule that is soluble in water within a predetermined temperature range.
- 5. A process according to any preceding claim, wherein the flavour is encapsulated in a polysaccharide that has adhesive properties.
- 6. A process according to claims 4 or 5 wherein the polysaccharide is a modified starch.
- 7. A process according to claim 6 wherein the polysaccharide is an n-octenyl succinate modified starch.
- 8. A process according to any one of claims 5 to 7, wherein the encapsulant material also performs as an emulsifier during the production of the encapsulated particles of flavour.

- 9. A process according to any one of claims 1 to 3, wherein the flavouring is encapsulated by a capsule that is frangible within a pre-determined temperature range.
- 10. A process according to claim 9, wherein the flavouring in the capsule is designed to increase in internal vapour pressure within said pre-determined temperature range so as induce rupture of said capsule.
- 11. A process according to claim 9 or 10, wherein the capsule has a gum-based coating that is designed to weaken in said temperature range so as to induce rupture of said capsule.
- 12. An infusion product comprising a porous carrier containing matter to be infused and encapsulated flavour particles bonded to said carrier by using a dosing process that controls the distribution of particles on the carrier.
- 13. An infusion product according to claim 12, wherein the encapsulated flavour particles comprise an outer capsule of polysaccharide with adhesive properties.
- 14. An infusion product according to claim 13, wherein the polysaccharide is a modified starch.
- 15. An infusion product according to claim 14 wherein the modified starch is an n-octenyl succinate modified starch.
- 16. An infusion product according to claim 13, wherein the polysaccharide is a natural gum.
- 17. An infusion product according to claim 16, wherein the capsule is frangible within a predetermined temperature range.

- 18. An infusion product according to claim 17, wherein the flavouring in the capsule is designed to increase in internal vapour pressure within said predetermined temperature range so as to induce rupture of said capsule.
- 19. An infusion product according to claim 17 or 18 wherein the capsule has a gum-based coating that is designed to weaken in said temperature range so as to induce rupture of said capsule.

INTERNATIONAL SEARCH REPORT

Application No PCT/GB 00/01160

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A23F3/40 A23L1/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 $\begin{array}{ll} \text{Minimum documentation searched (classification system followed by classification symbols)} \\ IPC 7 & A23F & A23L & B65B & B65D \\ \end{array}$

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, PAJ, EPO-Internal, FSTA

C. DOCUM	ENTS CONSIDERED TO BE RELEVANT	
Category '	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DATABASE WPI Section Ch, Week 198645 Derwent Publications Ltd., London, GB; Class D13, AN 1986-293635 XP002142239 & HU 39 343 A (CYCLOPACK KUTATASI),	1-3,5,6, 12,13
Υ	29 September 1986 (1986-09-29) abstract	7,8
X	EP 0 284 790 A (FIRMENICH & CIE) 5 October 1988 (1988-10-05) page 1, line 35 -page 2, line 49; claims 1-5; example 4 & US 4 880 649 A 14 November 1989 (1989-11-14) cited in the application	1,2,5-7, 9,11-14, 16,17
	 -/	

X Further documents are listed in the continuation of box C.	X Patent family members are listed in annex.
 Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filling date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed 	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family
Date of the actual completion of the international search	Date of mailing of the international search report
12 July 2000	25/07/2000
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Authorized officer Desmedt, G
	Journal of the second of the s

INTERNATION SEARCH REPORT

Ir Application No
PCT/GB 00/01160

0.40 =====	P(CT/GB 00/01160
C.(Continu	Citation of document, with indication where appropriate of the relievant	
	Citation of document, with indication where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5 603 971 A (POPPLEWELL LEWIS M ET AL) 18 February 1997 (1997-02-18) column 14, line 12 - line 20; claims 1,11; examples 9-11	7,8
Y	US 4 311 720 A (MARMO DON ET AL) 19 January 1982 (1982-01-19) claims 1-6; examples K,XLIII	7,8
A	US 5 094 860 A (NEWHALL RALPH P ET AL) 10 March 1992 (1992-03-10) the whole document & EP 0 499 858 A 26 August 1992 (1992-08-26) cited in the application	1
A	EP 0 084 708 A (UNILEVER PLC ;UNILEVER NV (NL)) 3 August 1983 (1983-08-03) example 22	1
İ		
ļ		

1

INTERNATIONAL SEARCH REPORT

Information on patent family members

In att Application No PCT/GB 00/01160

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
HU 39343	Α	29-09-1986	NONI	<u> </u>	<u> </u>
EP 0284790	Α	05-10-1988	AU CA DE DE JP JP US	608303 B 1339688 A 1336871 A 3883273 A 3883273 T 2672323 B 63301760 A 4880649 A	28-03-1991 29-09-1988 05-09-1995 23-09-1993 27-01-1994 05-11-1997 08-12-1988 14-11-1989
US 5603971	A	18-02-1997	US AU CA EP FI JP NO WO	5897897 A 6701694 A 2160684 A 0693884 A 954911 A 8509018 T 954071 A 9423593 A	27-04-1999 08-11-1994 27-10-1994 31-01-1996 16-10-1995 24-09-1996 13-10-1995 27-10-1994
US 4311720	A	19-01-1982	US CA	4253473 A 1119793 A	03-03-1981 16-03-1982
US 5094860	A	10-03-1992	AU CA EP	1110892 A 2060857 A 0499858 A	27-08-1992 21-08-1992 26-08-1992
EP 0084708	А	03-08-1983	AT AU AU BR CA DE US ZA JP JP JP	17552 T 551432 B 9096482 A 8206942 A 1191083 A 3268717 D 4471871 A 8208839 A 1629989 C 2045653 B 58109058 A	15-02-1986 01-05-1986 09-06-1983 04-10-1983 30-07-1985 06-03-1986 18-09-1984 25-07-1984 20-12-1991 11-10-1990 29-06-1983